

TURBO 50/80

ELECTROMECHANICAL GEAR MOTOR FOR SLIDING GATES FROM 500 Kg TO 800 Kg, 230 Vac



PLUS

With slowdown function both in opening and closing to preserve gate integrity

Electronic and mechanical parts well protected from external agents

Easy maintenance thanks to the horizontal control unit position

With fixing plate included

With 230 Vac control unit CT102 (pag. 142 for technical details)



LCD display



Sturdy and performing motors



High quality ball bearing

MODELS

CODE	DESCRIPTION	PCS PALLET
SC52	For sliding gates up to 500 Kg, 230 Vac motor, control unit with slowdown and electric limit switch (1 pc)	36
SC82	For sliding gates up to 800 Kg, 230 Vac motor, control unit with slowdown and electric limit switch (1 pc)	36

		SC52	SC82
MECHANICAL DATA			
speed	cm/s	16	16
torque	Nm	16	23
working cycle	%	30	30
ELECTRICAL DATA			
control board		CT102	CT102
power	Vac	230	230
consumption	A	1,3	1,9
absorbed power	W	300	450
capacitor	µF	12,5	16
thermoprotection	°C	150	150
GENERIC DATA			
protection degree	IP	44	44
dimensions (L - D - H)	mm	320 - 184 - 260	320 - 184 - 260
weight	kg	12	12,5
working temperature	°C	-20 + 55	-20 + 55
gate maximum weight	Kg	500	800

ACCESSORIES



CREM-P
M4 nylon toothed
rack L=1000 mm
for gates up to
max 800 kg

PCS 10



CREM-8
M4 iron toothed
rack 30x8 mm
L=1000 mm

PCS 4



CREM-12
M4 iron toothed
rack 30x12 mm
L=1000 mm
(for SC82)

PCS 4



TS
Warning board

PC 1